

155TS2

NEXT GENERATION HAULING

For operators with horsepower to spare, the 155 series scraper fits the bill. You will also benefit from the additional capacity over other agricultural earthmovers. Designed for MFWD & articulated 4WD Tractors, available in a Front or Rear configuration.

BUILT FOR YOUR UNIQUE DEMAND

The 155TS2 was created for customers who asked for added capacity, ease of transport, and increased cut width. We kept it within budget and were still able to add in all the bells & whistles. Standard options include high flotation tires, GPS ready framework, 5 piece blade set and a ride control hydraulic accumulator.



The 155TS2 sets the standard for this class of machine. Most notable are the standard features: an ejector cylinder with a thicker rod and barrel, large tires to run through anything, and beefed up trailing arms that will take the abuse.

155TS2
15.5 cu. yd - 250 +HP. - Ejector - Direct Mount

155TS2

HITCH

Our signature MDU hitch is a rugged and draw-bar-compatible attachment point. With the ability to swivel on a multiple axis, promising a smooth ride.

Ashland also offers a full line of drawbars to fit any tractor or implement hitch.



FRONT SECTION

The best part about a direct-mount scraper is that the Front Section provides weight transfer to the tractor. Requiring less horsepower to load the same amount of material. And with one pivot point, backing up is dead simple – maneuvering is no longer a problem.



The Pole is comprised of two formed high grade steel plate halves. Add our thick wall front pipe and it's the strongest unit out there.



APRON

Fabricated from heavier, high grade steel the 155 Apron mates perfectly with the machine. We have added stronger side pockets. The main actuating joint is fitted with a 45-degree pocket for added strength. Even a viewing window has been placed on the front to monitor what is happening within the Bowl.



BOWL

All outboard supports are fitted with 45-degree pockets that add strength where it's needed most. The dirt shields and side walls have been thickened to better protect against falling debris. With the dual plated floor, stumps and large rocks are no match. It's added rigidity for your toughest work.



The extra thick 5-piece blade set and over-sized plow bolts are of the highest quality. You will easily cut through the heaviest material.



PUSHOFF

Ashland has eliminated side scrubbing by using stepped-rollers and added supports to the pushoff. The rear guides are also made of steel and run on a wide track. With the improved single ejector cylinder and redesigned push-off frame you can quickly unload stubborn soil.



CYLINDERS

The ejector cylinder is made with a heavy wall barrel, larger rod, and thicker seals. This cylinder withstands greater forces than ever before. Also, the lift cylinders used are the ever-popular trunnion style. Solid end caps, lugs, and bands to handle high speeds and heavy loads.



Ashland has been manufacturing scrapers for over 60 years. Offering dolly wheel, direct mount, ejectors, and dump style scrapers. The 155TS2 fits that niche of size, versatility, and maneuverability that operators are after. See for yourself why it has stood the test of time.

SPECIFICATIONS

Capacity, Heaped (ISO 6485):	15.5 cu. yd.
Required HP:	250 - 620
Width of Cut:	108.5"
Apron Clearance:	62"
Ejector Cylinder (2):	5" x 60" Stroke
Apron Cylinder (1):	4" x 13" Stroke
Lift Cylinder (2):	5" x 20" Stroke
Laser/GPS Bracket:	Standard
Tires (Std. Rear (2)):	29.5 x 25
Overall Width:	120"
Overall Length:	360"
Overall Height:	102"
Weight (Front Config.):	21,800 lbs.
Weight (Rear Config.):	21,300 lbs.

Your Dealer

DO MORE.

46°35'53.3"N 90°50'25.5"W
P.O. Box 717 1115 Rail Dr.
Ashland, WI 54806 USA

Toll Free - 877 . 634 . 4622
Direct - 715 . 682 . 4622 ext 610
Email - sales@ashlandind.com

Web - www.ashlandind.com
Scraper Drawbars - www.scraperdrawbar.com
© 2016 Ashland Industries Printed USA