



# TATU 8013 GAPM HD

HEAVY DUTY HINGE OFFSET DISK HARROW



Leaders in your field



## SPECIFICATION

Disc Blade Dimensions

**32" x 1/2"**  
**812 mm x 12 mm**

Disc Spacings (mm)

**13"**  
**330 mm**

Weight Per Disc (kg)

**285 kg**

Working Width

**10"**  
**3.1 m**

Axle Diameter

**2 1/2"**  
**63.5 mm**

## MODEL VARIATIONS

Discs	Width (mm)	Weight Per Disc (kg)	Net Weight (kg)	HP Requirement
<b>16</b>	<b>3,100</b>	<b>285</b>	<b>4787</b>	<b>205 - 220</b>

Measurements are best estimate

# Power & Earth®

Leaders in your field



Articulated drawbar  
for easier transportation


The model **8031 GASPM EHD** is specially designed to meet the extreme conditions in construction, road building, deep tillage, tilling new ground and recently deforested land.



Rod stops to adjust the gang angle



- SPECIAL OIL BATH BEARING ASSEMBLIES
- TAPERED BEARINGS AND DUO-CONE TYPE SEALS
- THE LIFE OF YOUR DISK HARROW REQUIRES ORIGINAL TATU REPLACEMENT PARTS



## STANDARD FEATURES

- TATU oil bath bearings assemblies with tapered roller blade and duo-cone seals
- ½" x 5" x 10" gang carriers, reinforced through two welded "U" profile
- 2½" round heat treated alloy steel gang axles
- Heavy steel disc spacer spools
- Heat treated boron steel disc blades, notched front and rear
- Heavy duty disc blade scrapers
- Stabilizer bar front and rear disc gangs leveling
- Perforated offset bar to allow lateral adjustments under varying draft conditions
- Box type construction drawbar with standard draw bar plates
- Adjustable gang axles up to 42 degrees
- Removable bushings on articulated points